

# Improving Public Access

**This is an old version of the page**

**This is an old version of the page**

**Date published: 12 May, 2015**

**Date superseded: 8 March, 2016**

Updates to last version

- change to information on spatial targeting

## Aim

The aim of this item is to support new and upgraded paths for public use, providing:

- improved links and connectivity
- improved path conditions
- barrier-free access for all

These new and improved paths – core paths, links to core paths, and paths connecting to wider local networks and longer paths – will encourage responsible public outdoor access for the full range of users, and help to integrate access and recreational use with good land management.

This will generate wide benefits

- health improvement and increased physical activity
- a sustainable resource for nearby communities, visitors and enterprises
- in fostering broad social and economic opportunities through enhanced outdoor access and recreation

## Eligibility

This item is open to local authorities and administrations, public bodies, public-private partnerships, NGOs, private companies, organisations in charge of tourist and recreational development, as well as individual farmers, groups of farmers and other land managers.

## Spatial targeting

This item is available across all rural areas of Scotland, which is defined as land other than settlements with a population of over 3000.

## Application requirements

As part of the application you must prepare and include a map showing the relevant access context (existing core paths, other local paths, key access / arrival points, any long-distance paths, key features of interest, etc) both within the application unit and in the relevant surrounding areas.

The map must also show the locations of all the proposed access works. Note that as part of the application assessment process, this map will be copied to your local authority or national park authority access staff for information / verification.

You will be asked to describe and explain the benefits to connectivity and local objectives arising from your proposal, and how it will add value for the locality.

## Requirements

### **Connectivity**

You must establish a new path, or carry out improvements to an existing path, in one of the following categories:

- a core path or a link to a core path, or
- a path providing access to a feature of interest (e.g. viewpoint, loch, riverside, cultural / historic feature etc), or
- a path which links to other paths at the boundaries of your land, to form effective and convenient parts of wider local path networks or of a long distance path

### Technical specification

You must ensure the new or upgraded path is:

- well-drained
- surfaced with whinstone / granite dust or a semi-bound (e.g. Toppet) surface
- normally 1.8 metres in width, but path width may be varied within a range from 1.2 to 2.5 metres if that is justified by the anticipated volume of use
- signposted
- where bridges and boardwalks are established, these must be of sufficient width as in the technical specification to be DDA / Equality Act compliant
- not for motorised use; tarmac surfacing is also ineligible

### Barrier free

The new or upgraded paths, as far as practicably possible, should provide ramps in place of steps (e.g. on bridge approaches), and self-closing gates (not stiles or kissing gates) for DDA / Equality Act compliance, thus being suitable for use by walkers, cyclists, horse-riders and wheelchairs / mobility scooters, and not for motorised use.

## Payment

You can claim the standard capital cost per unit for approved items, as stated in outline in the table below (with links to a detailed specification where relevant). These costs include labour (direct or contract) and materials.

### Table of standard costs (with outline specification)

	Capital Item	Outline Specification (click on the name of each item to see the full specification)	Standard cost per unit for labour and materials
<b>Public path infrastructure</b>			
1	<a href="#">New path – unbound surface</a>	For the construction of a new path with unbound surface (whinstone / granite dust) path, with full tray excavation, or half tray and geotextile.	£18.20 / square metre
2	<a href="#">New path – semi-bound surface</a>	For the construction of a new path with semibound surface, of recycled semi-binding materials, with full tray excavation or half tray and geotextile.	£28.15 / square metre
3	<a href="#">Upgrade to an existing path</a>	For the scraping of an existing footpath and construction of a fresh sub-base, and path surfacing of whinstone / granite dust.	£6.20 / square metre
4	<a href="#">Self-closing two-way opening gate</a>	To install a two-way opening, self-closing gate (galvanised steel or timber) of 1.5 metres width. A gate also performs as a vehicle barrier.	£440 / gate
5	<a href="#">Self-closing, one-way opening gate</a>	For installing a one-way opening, self-closing gate (galvanised steel or timber) of 1.5 metres width. A gate also performs as a vehicle barrier.	£350 / gate

6	Path bridge	To provide a path bridge, in accordance with the ' <a href="#">Path Bridges</a> ' guide.	£1,100 / square metre of clear user deck
7	<a href="#">Gabion basket retaining wall for path</a>	Construction of metal mesh stone-filled gabion baskets to create revetments for the purpose of stabilising new or upgraded paths.	£100 / cubic metre
8	<a href="#">Boardwalk</a>	For a wooden or recycled plastic boardwalk with edge rails, giving a clear user width of at least 1.2 metres.	£91 / square metre of clear user deck
9	<a href="#">Timber board and aggregate steps</a>	For the installation of steps, only in exceptional situations where the terrain naturally restricts access, and a ramped path cannot reasonably be provided without exceeding ramp gradient limits of 1:12.	£150 / metre
10	<a href="#">Drainage ditch</a>	For drainage in conjunction with the path construction or upgrading, as an open machine-dug V or U ditch, 200 to 300 millimetres deep with stable angled sides.	£1.88 / metre
11	<a href="#">Piped culvert (300 millimetre pipe)</a>	For a 300 millimetre twin-wall plastic culvert pipe with built stone headwalls that is required in conjunction with the path construction or upgrading.	£143 / each
12	<a href="#">Piped culvert (450 millimetre pipe)</a>	For a 450 millimetre twin-wall plastic culvert pipe with built stone headwalls that is required in conjunction with the path construction or upgrading.	£395 / each
<b>Seats and signs</b>			
13	<a href="#">Perch seat</a>	For a timber perch seat alongside the new or upgraded path.	£200 / each
14	<a href="#">Timber bench</a>	For a bench without a backrest on a level and surfaced area close to the new or upgraded path.	£350 / each
15	<a href="#">Timber picnic table</a>	For a wooden picnic table with easy-access bench seats without backrests, on a level and surfaced area close to the new or upgraded path	£700 / each
16	<a href="#">Fingerpost</a>	For a finger post to indicate the path direction / destination / distance, with hollow steel post and aluminium finger blades.	£150 / each
17	<a href="#">Waymarker post</a>	For a treated and routed timber waymarker post, including disc / arrow as needed.	£29 / each
18	<a href="#">A3 on-site information panel</a>	For a laminated A3 panel sign mounted on wooden post(s), to provide path grading and route information to national standard	£262 / each
19	<a href="#">Entrance sign</a>	For a timber roadside entrance sign, with painted background and routed and painted lettering.	£270 / each
20	<a href="#">Stock fencing</a>	For fencing associated with the new or upgraded path, with posts set no more than 3.5	£5.50 / metre

		metres apart, minimum of six line wires or two line wires with woven wire netting, and any barbed or electrified wire on the field side protected by a plain wire on the path side.	
	<b>Tree safety</b>		
21	<a href="#">Tree safety survey</a>	For the works required to undertake a survey and report on high risk trees or woodland affecting the new or upgraded paths, especially those that will experience high visitor numbers.	£33 / hectare
22	<a href="#">Make safe hazardous mature trees</a>	For the labour and machinery required for the removal of trees, deadwood and other dangerous tree features identified in the tree safety survey as posing a significant risk to users of the new or upgraded path.	£113 / tree
23	<a href="#">Manual brashing</a>	For the works required to remove the lower branches of trees in areas of high use along both sides of new or upgraded paths.	£1.09 / metre

Table of standard costs (with outline specification)

## [Previous guidance](#)

[Previous versions of this page](#)